


## Declaration of performance

### According to Regulation (EU) No. 305/2011 N. EK195

- |  |   |
|--|---|
| 1. Unique identification code of the product-type  | <b>MYRNA / MYRNA Q</b>  |
| 2. Intended uses of the product in accordance with the applicable harmonized technical specification | Appliance for domestic heating, fuelled with wood pellet, without hot water production          |
| 3. Name or trade mark of the manufacturer (Article 11-5)   | EDILKAMIN S.p.A.<br>Via Mascagni, 7 – 20020 Lainate (MI)<br>tel. 02 937621 – mail@edilkamin.com |
| 4. Name and address of the agent (Article 12-2)  |   |
| 5. Assessment and verification system for constancy of performance (Annex 5)                         | System 3  |
| 6a. Harmonized technical specification<br>Laboratory notified  | EN 14785:2006<br>Kiwa Cermet italia, NB 0476  |
| 7. Declared performance  |   |

Essential characteristics	Performance	
Reaction to fire	A1	
Distance to combustible materials (minimum distance in mm)		Rear = 100 Sides = 100 Front = NPD Ceiling = NPD Floor = NPD
Risk of burning fuel falling out	Pass	
Emission of combustion products	Rated fuel load	Reduced fuel load
CO (ref. at 13% O <sub>2</sub> )	24,3 mg/Nm <sup>3</sup> - 0,0019%	127 mg/Nm <sup>3</sup> – 0,0102%
NO <sub>x</sub> (ref. at 13% O <sub>2</sub> )	127,5 mg/Nm <sup>3</sup>	103 mg/Nm <sup>3</sup>
OGC (ref. at 13% O <sub>2</sub> )	2 mg/Nm <sup>3</sup>	3,1 mg/Nm <sup>3</sup>
Particulate matter (ref. at 13% O <sub>2</sub> )	6 mg/Nm <sup>3</sup>	11,7 mg/Nm <sup>3</sup>
Surface temperature	Pass	
Electrical safety	Pass	
Cleanability	Pass	
Maximum operating pressure	- bar	
Mechanical resistance (to carry a chimneyflue)	NPD	
Thermal output	Rated fuel load	Reduced fuel load
Nominal heat output	10 kW	3,5 kW
Nominal space heating output	10 kW	3,5 kW
Nominal boiler output (to water)	--- kW	--- kW
Energy efficiency	91,4 %	94,7 %
Flue gas temperature	T[136°C]	T[75°C]

- |   |         |
|---|---------|
| 8. Test report number (based on System 3) | 2004592 |
|---|---------|

The performance of the product identified in point 1 is in conformity with the declared performance in points 6a and 7  
 This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Lainate, 30/09/2020

Signed for and on behalf of Edilkamin S.p.A. by:

Legal Representative

Luca Borsatti

