



*APERTURA FOCOLARE PER RIVESTIMENTO

B SEMITRANCI Ø100-150

C INGRESSO ARIA COMBURENTE Ø 150



EN 13229

BlmSchV Stufe 2

Regensburger BStV / Aachener BStV / Munchener BStV

LRV

4 stelle DM.186



flamme
VERTE

(Max) nominal heat output	12.6 kW
Efficiency at Max	77.6 %
Energy Efficiency Class (A++ / G scale)	A
Energy Efficiency Index (EEI)	103 %
Seasonal space heating energy efficiency (ηs)	68 %
Temperature of exhaust smoke at Max	272 °C
Particulate/OGC / Nox (nominal at 13%O2)	30 - 46 - 132 mg/Nm3
CO at 13% O₂ at Max	0.1 %
CO₂ at Max	8.6 %
Mass of smoke at Max	12.1 g/sec
Fuel dimensions	L 250 ÷ 330mm
Hourly consumption at Max	3.8 kg/h *
Heatable volume m3	229 - 360 - 630 **
Combustion air inlet	Ø 150 mm
Air inlet	180 cm2
Smoke outlet	Ø 200 mm
Net weight	334 kg
Distance from combustible material (back/side/under)	1900 mm / 160 mm / 220 mm
Distance from combustible material (front/ceiling)	800 mm / 1900 mm

* Data that may vary depending on the type of pellets used.

**Heatable volume based on the requested power per m3 (respectively 55-35-20 W/m3)