

Pellet Air

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,5 - 5,5
Introduced thermal power (at max)	kW	6,1
Seasonal energy efficiency	η_s [%]	86
Useful efficiency (at min-at max)	%	91,0 - 90,0
Heating surface (at min-at max)	m ²	26,4 - 58,1
CO ₂ (min-max)	%	0,0 - 11,7
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	238 - 140
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	2 - 4
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	140 - 129
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	20 - 15
Combustible Pellet	mm	Ø6 L3÷40
Hopper capacity	kg	11
Hourly consumption (at min-at max)	kg/h	0,60 - 1,30
Autonomy (at min-at max)	h	18 - 8
Supply and frequency	V-Hz	230-50
Ignition electrical absorption (at max)	W	345
Operating electrical absorption (at max)	W	49
Chimney flue depression (at min-at max)	Pa	2 - 12
Mass of smoke (at min-at max)	g/sec	2,6 - 3,9
Exhaust fumes temperature (at min-at max)	°C	113 - 163
Distance from material comb. (back/side/under)	mm	200 / 300 / 0
Distance to material comb. (front/top)	mm	1000 / 0
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	130
Ducting outlet (C)	Ø mm	0
Ductable up to	m	0

PLUS

- Sealed Chamber
- Magic Glass
- Cast iron burning pot
- Comfort mode - Maximum silence
- Integrated Wi-Fi and Bluetooth
- Connection to the external therm.
- Weekly programming
- Upper exhaust

AVAILABLE FINISHES

7021058		Steel White	EAN 8053859013747
7021059		Steel Titanium	EAN 8053859013754
7021061		Steel Anthracite	EAN 8053859013778


CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen

EN 14785:2006



STOVE PACKAGE



L (cm)	H (cm)	P (cm)
80	117	60
Volume (m ³)	0,56	
Gross weight (kg)	86	
Net weight (kg)	76	

STORAGE



N° (max)
2

TRANSPORT



66 pz