

TOULOUSE S



wood or pellet without electricity

Technical specifications of the accumulating heater:

measurements (cm)	width	height	depth
stove	61,5	116	48,5
combustion chamber	37	30	29
fire glass	34	42	
fire door	45	53	
flue pipe connection height to top pipe soci outside air connection	98		
height to mid connection horizontal			35
depth to mid connection vertical			13,5

depth to find connection vertical			15,5
total weight	chamotte bricks	heat accumulator	
253 kg	26 kg	40 kg	
data for	pellet box S	pellet box XL	wood
nominal heat output	7,5 kW	11 kW	6,5 kW
output range	7,5 - 5 kW	11 - 8,5 kW	6,5 - 3,3 kW
efficiency	87%	85%	87%
heating capability*	50 - 150 m³	70 - 250 m³	70 - 250 m³
amount of fuel	3,8 kg	7,5 kg	2,9 kg / h
fire duration	up to 2,5 h	up to 5 h	up to 5 h
heat release	up to 10 h	up to 13 h	up to 13 h
flue gas flow volume	8,97 g/s	10,74 g/s	10,3 g/s
exhaust °C (nozzle)	180 °C	230 °C	268°C
min/max feed press.	12 / 15 Pa	13 / 15 Pa	12 / 15 Pa
CO (13%/O2) [mg/m³]	1166	880	1074
CO (13%/O2) [%]	0,093	0,070	0,086
dust (13%/O2) [mg/m	36	30	31
NOx (13%/O2) [mg/m³]	109	110	110
CxHy (13%/O2) [mg/m³]	54	41	51
wall distance, rear	15 cm	20 cm	15 cm
wall distance, side	15 cm	15 cm	15 cm
distance to the front	80 cm	80 cm	80 cm

Fulfils the latest standards in burning wood, wood-briquettes and pellets (please see appliacable standards).

Please check the instruction manual for this wood & pellet burning stove.


Suitable for multiple chimneys.


* depending on stove location in the living area, room isolation, height of the room and amount of fuel


Subject to alterations; errors including printer's errors.

Our specialised stove builders and retailers will assist you with practical advice.

NEW MODEL







Other stone applications on request!

Heat-storing stove, model Toulouse S

ENR	model	delivery time			
153-2001	Toulouse S ↑	3			
	· front anthracite				
	· side panels and lid				
	natural stone grey chiselled				
153-2019	Toulouse S ↑	3			
	· front anthracite				
	· side panels and lid				
	natural stone light grey blasted				
153-2007	Toulouse S ↑	3			
	· front anthracite				
	· side panels and lid				
	natural stone cream blasted				
153-2013	Toulouse S ↑	4			
	· front anthracite				
1	· side panels and lid				
	aus sandstone clouded				
153-2025	Toulouse S ↑	4			
	· front anthracite				
	· side panels and lid				
	natural stone black smooth				
	with excellent heat-storing-capabilities				
	outside air connection possible:				
	Be sure to specify when ordering:				
	outside air connection horizontal or vertical				
	(is included in scope of delivery)				
	without electricity				
552-2014	pellet box S with 7,5 kW (at purchase with a stove)				
	pellet box S with 7,5 kW (retrofit kit)				
552-2004	pellet box XL with 11 kW (at purchase with a stove)				
	pellet box XL with 11 kW (retrofit kit)				
	· made of heat-resistant stainless steel				
	· at type S with 2, at type XL with 3				
	black ceramic specialised glasses				
	· with lighter, silicone gloves, pellet-felt bag up to 20 kg,				
	cleaning brushes, pellet shovel provided				
Accessories	& spare parts (Important! Always specify se	rial number!)	-		
303153-916	additional heat accumulator (2 pcs, 40 kg)				
303 136	combustion chamber chamottes (set) 1. BImSchV le	evel 2			
200 100	,				
308 139	fire glass incl. gasket set				
307 010	glass seal combustion chamber				
303 010	door seal combustion chamber				
912 007 0005	thermic glue 1100 °C (17 ml tube)				
29 119 311	floor protector stainless steel (see accessories)				
29 119 311	floor protector stainless steel (see accessories)				
∠7 117 4 UU	floor protector glass (see accessories)				
			i e e e e e e e e e e e e e e e e e e e		
	For other connection accessories, please see list of a	accessories.			