

Edilkamin S.p.A. 20020 Lainate (MI), via P. Mascagni 7 Tel. +39 02 937621 Fax +39 02 93762 400/300 mail@edilkamin.com www.edilkamin.com

Capitale € 4.100.000 int. vers.
Sede legale:
20123 Milano, via Vincenzo Monti 47
Reg. Imp. di Milano 00192220192
REA n° 878888
Cod. Fiscale e Partita IVA 00192220192

## **Declaration of performance**

According to Regulation (EU) No. 305/2011

N. EK166

1. Unique identification code of the product-type

2. Intended uses of the product in accordance with the applicable harmonized technical specification

3. Name or trade mark of the manufacturer (Article 11-5)

4. Name and address of the agent (Article 12-2)

5. Assessment and verification system for constancy of performance (Annex 5)

6a. Harmonized technical specification Laboratory notified

7. Declared performance

## **BILD ATC**

Appliance for domestic heating, fuelled with wood pellet, without hot water production EDILKAMIN S.p.A.

Via Mascagni, 7 – 20020 Lainate (MI) Italy

Via Mascagni, 7 – 20020 Lainate (MI) Italy tel. +39 02 937621 – mail@edilkamin.com

System 3 and System 4

EN 14785:2006

TÜV Rheinland Energy GmbH - NB2456

. Declared performance		
Essential characteristics	Performance	
Reaction to fire	A1	
Distance to combustible materials	<b>▲</b> C Rear = 0	
(minimum distance in mm)	R _ Sides = 150	
	Front = 800 Ceiling = NPD Floor = NPD	
Risk of burning fuel falling out	Pass	
Emission of combustion products	Rated fuel load	Reduced fuel load
CO (ref. at 13% O <sub>2</sub> )	235 mg/Nm <sup>3</sup> - 0,019%	204 mg/Nm <sup>3</sup> – 0,016%
NOx (ref. at 13% O <sub>2</sub> )	148 mg/Nm <sup>3</sup>	158 mg/Nm <sup>3</sup>
OGC (ref. at 13% O <sub>2</sub> )	8,0 mg/Nm <sup>3</sup>	7,0 mg/Nm <sup>3</sup>
Particulate matter (ref. at 13% O <sub>2</sub> )	19,8 mg/Nm <sup>3</sup>	19,0 mg/Nm <sup>3</sup>
Surface temperature	Pass	
Electrical safety	Pass	
Cleanability	Pass	
Maximum operating pressure	- bar	
Mechanical resistance (to carry a chimneyflue)	NPD	
Thermal output	Rated fuel load	Reduced fuel load
Nominal heat output	9,1 kW	4,4 kW
Nominal space heating output	9,1 kW	4,4 kW
Nominal boiler output (to water)	- kW	- kW
Energy efficiency	89,0 %	91,6 %
Flue gas temperature	T[160°C]	T[103°C]

8. Test report number (based on System 3)

K23292018T1

The performance of the product identified in point 1 is in conformity with the declared performance in points 6a and 7 This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Lainate, 25/06/2018

Signed for and on behalf of Edilkamin S.p.A. by:

Legal Representative

Dott. Stefano Borsatti